
## **ESD-Tischmatte Anti-Stat**







- Vinyl work surface that dissipates static from conductive items placed on it.
- Protects table and keeps sensitive components safe from damaging static shocks.
- Smooth top surface that is abrasion resistant and easy to wipe clean with recommended art. 057.
- Optional 10 mm female socket attached to the mat for connection with recommended common grounding point cord art. 052.
- Meets EOS/ESD-S4, measured resistance for work surfaces Rg  $10^7$  and Rp  $10^8$   $\Omega$ .
- Electrostatic charge (walking test), meets ISO6356 and EN1815.
- Free of toxic DOP and DMF.



## **ESD-Tischmatte Anti-Stat**

|                                | PI  | RODUCT SPECIFICATIONS  |  |  |
|--------------------------------|---|--|--|--|
| Designation                    | ESD Protective Mat  |  |  |  |
| Туре                           | Bench mat for work surfaces                                     |  |  |  |
| Description                    | Table protective mat, smooth top surface abrasion resistant     |  |  |  |
| Material                       | Microcellular vinyl, treated with dissipative static properties |  |  |  |
| Process                        | Foaming   |  |  |  |
| Category                       | Better  |  |  |  |
| Recommended use                | Under electrostatic sensitive components                        |  |  |  |
| Colours                        | Blue  |  |  |  |
| Weight                         | 3 kg/m²   |  |  |  |
| Thickness                      | 6.4 mm  |  |  |  |
| Standard sizes                 | 76 cm x 12.2 m<br>91 cm x 12.2 m                                |  |  |  |
| Custom sizes                   | 76 cm, 91 cm, per linear r                                      | 76 cm, 91 cm, per linear meter   |  |  |
| Special remarks                |   | Meets EOS/ESD-S4, measured resistance for work surfaces RG 10 $^7$ $\Omega$ and RP 10 $^8$ $\Omega$ . Electrostatic charge (walking test) meets ISO6356 and EN1815 |  |  |
|                                |   | PRODUCT TESTING  |  |  |
| Tests                          |   | Norms  | Results                                |  |
| Compression deflection         |   | U.S.   |  |  |
|                                | 1.4 kg/cm <sup>2</sup>  |  |  |  |
|                                | 2.8 kg/cm <sup>2</sup>  |  |  |  |
| Foam battery                   |   | ASTM D3574   |  |  |
| Abrasion resistance            |   | ASTM D3884-01  |  |  |
|                                | 500 Cycles  |  |  |  |
|                                | 5000 Cycles   |  |  |  |
| Static coefficient of friction |   | ASTM C1028-96  |  |  |
| Elongation                     |   | ASTM D412  |  |  |
| Breaking load                  |   | ASTM D412  |  |  |
| Graves tear strength           |   | ASTM D 1004  |  |  |
| Hardness                       |   | ASTM D2240-02  |  |  |
| Anti-slip                      |   | DIN 51130 and BG-RULE BGR181   |  |  |
|                                |   | FIRE TESTING   |  |  |
|                                | Critical radiant flux   | ASTM E-648   |  |  |
|                                | Fire retardence   | DIN4102  |  |  |
|                                | Fire retardancy   | EN 13501-1   | CFL - S1                               |  |
|                                | Flammability test   | ASTM D2859   |  |  |
| ESD                            |   | ANSI ESD S7.1<br>50% Humidity  | RG 9.2 x $10^7$ Ω<br>RP 1.7 x $10^7$ Ω |  |
| Sustainability                 |   | <ul> <li>Recyclable material</li> <li>Reach Compliant (Registration, Evaluation, Authorization and<br/>Restriction of Chemicals)</li> </ul>                        |  |  |

Zu beziehen bei: Matten-Zuschnitt.de, Tel. 0 63 59/9611 906, info@matten-zuschnitt.de