

Antirutschläufer Mineral-Grit



- Gritted anti-slip rolls feature oil resistant vinyl with mineral coating for slip prevention in extremely wet or oily areas.
- Lightweight and loose lay for a quick and easy anti-slip solution.
- Slip resistant vinyl backing.



PRODUCT SPECIFICATIONS		
Designation	Specialty floor products	
Type	Anti-slip gritted mat	
Description	Anti-slip surface	
Material	Disilicon trioxide	
Process	N/A	
Category	N/A	
Recommended use	Loose lay in extremely slippery areas for a quick anti-slip solution.	
Colours	Black	
Weight	2.3 kg/m ²	
Thickness	2.1 mm	
Standard sizes	Black: 90 cm x 150 cm 90 cm x 18.3 m	
Custom sizes	90 cm x linear meter	
Special remarks	Oil resistant	
PRODUCT TESTING		
Tests	Norms	Results
Compression deflection	U.S.	
	1.4 kg/cm ²	
	2.8 kg/cm ²	
Foam battery	ASTM D3574	
Abrasion resistance	ASTM D3884-01	
	500 Cycles	
	1000 Cycles	
Static coefficient of friction	ASTM C1028-96	
Elongation	ASTM D412	
Breaking load	ASTM D412	
Graves tear strength	ASTM D 1004	
Hardness	ASTM D2240-02	
Anti-slip	DIN 51130 and BG-RULE BGR181	
FIRE TESTING		
	Critical radiant flux	ASTM E-648
	Fire retardancy	DIN4102
		EN 13501-1
	Flammability test	ASTM D2859
ESD	ANSI ESD S7.1	
	50% Humidity	

Zu beziehen bei:
 Werkzeug-Profi.net | Matten-Zuschnitt.de
 info@werkzeug-profi.net, 0 63 59/96 11 906